



PREMIUM QUALITY

MADE IN ITALY



TORCHES & WELDING ACCESSORIES
MIG / MAG – TIG

GENERAL CATALOG

www.delfoweld.com



QUALITA' E DESIGN

DA SEMPRE

SONO LA NOSTRA

STORIA



SERVICE & QUALITY





QUALITY & DESIGN

ALWAYS OUR

HISTORY

PREMIUM QUALITY

MADE IN ITALY

ABOUT US

"DELFO S.r.l." it's a new name proposed by a board that started operating in this sector in 1973 founding OCIM S.r.l. (first Italian manufacturer of Mig-Tig torches) The aim of the new company will be the development of new products in order to maintain and further overcome the quality standard that has always distinguished us.

INNOVATION

Innovation and quality are the foundations on which the company is focused, to achieve these objectives Delfo S.r.l. invests significant human and financial resources in the development of new products in order to offer advanced technical solutions.

PRODUCTION

Thanks to the passion and experience gained over 45 years in welding market, we can define Delfo as a leader in the design and construction of special torches, both Air and Water cooled, with unique characteristics that meet the welder's needs.

DISTRIBUTION

Delfo's products are distributed through a dense network of specialized welding dealers.



TABLE OF CONTENTS

DELFO MIG - AIR

AIR COOLED TORCHES

DM. 2	NEW	6
DM. 3	NEW	7
DM. 4	NEW	8
TW. 2	NEW	9
TW. 4	NEW	10

DELFO MIG - LIQUID

LIQUID COOLED TORCHES

DM. 27	NEW	12
DM. 30	NEW	14
DM. 50	NEW	14
DM. 55	NEW	16

DELFO TIG - AIR

AIR COOLED TORCHES

DT. 9 / 9V	NEW	19
DT. 17 / 17V	NEW	20
DT. 26 / 26V	NEW	21

DELFO TIG - LIQUID

LIQUID COOLED TORCHES

DT. 19	NEW	23
DT. 20	NEW	24

DELFO MIG - AIR

AIR COOLED TORCHES

BEING DIFFERENT

PREMIUM QUALITY

MADE IN ITALY

- » New ergonomic handle with "Grip" insert for best accessibility - optimum balance.
- » New gas diffusers with metallic protection, for greater durability and heat resistance.
- » New ball joint with optimum movement radius.



DM.2 - DELFOMIG - AIR

AIR COOLED TORCHES




DM.2 DELFOMIG AIR


TECHNICAL DATA

Technical data:	(EN60974-7)
Rating CO²:	260A.
Rating mixed Gas (M21):	200 A.
Duty Cycle:	60%
Wire Size:	Ø 0,8-1,2 mm

SET 1 - TIP M8X30



SET 2 - TIP M6X30



SET 1 - TIP M8X30

COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM2.3	500.050.307	3 m.
DM2.4	500.050.407	4 m.

SET 2 - TIP M6X30

COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM2.3	500.040.307	3 m.
DM2.4	500.040.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Stnd. Øi. 15	179.105.110	5	23*	4,0 m. Liner for wires Ø 1,0/1,2	130.050.402	1
2	Tapered Nozzle Øi. 12	179.109.107	5	23	3,0 m. Liner for Al. wires Ø 0,8/1,0 Teflon	134.110.302	1
3	Cylindric Nozzle Øi. 18	179.104.105	5	23	4,0 m. Liner for Al. wires Ø 0,8/1,0 Teflon	134.110.402	1
5	Contact Tip M8x30 CU Ø 0,8	147.010.308	25	23	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
5*	Contact Tip M8x30 CU Ø 1,0	147.010.310	25	23	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
5	Contact Tip M8x30 CU Ø 1,2	147.010.312	25	23	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
5	Contact Tip M8x30 CU-CR-ZR Ø 0,8	147.020.308	25	23	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
5	Contact Tip M8x30 CU-CR-ZR Ø 1,0	147.020.310	25	24	Locking ring	127.102.102	5
5	Contact Tip M8x30 CU-CR-ZR Ø 1,2	147.020.312	25	25	Euro Connector	142.105.107	1
6	Gas Diffuser	118.102.111	5	26	Liner Nut	117.101.101	10
7	Elastic Ring	101.101.104	20	29	Spring (handle side)	141.106.116	1
8	Torch body with insulator	516.103.005	1	30	Spring (connector side)	141.106.107	1
9	Wukon insulating tube	140.104.130	1	32	Connector locking ring	127.105.101	1
11	Handle "DM" series	537.100.111	1	33	Knuckle joint	156.102.109	1
12	Handle case screw	181.103.108	20	34A	Nozzle Stnd. Øi. 13	179.105.103	5
13	Complete bladeswitch	146.101.112	5	34B	Tapered Nozzle Øi. 11	179.109.102	5
19	Complete coaxial cable 3m.	508.250.302	1	34C	Cylindric Nozzle Øi. 16	179.104.102	5
19	Complete coaxial cable 4m.	508.250.402	1	35	Contact Tip M6x30 CU Ø 0,8	147.010.208	25
20	Back cable support	156.101.103	1	35	Contact Tip M6x30 CU Ø 1,0	147.010.210	25
21	Back cable support screw	181.106.101	20	35	Contact Tip M6x30 CU-CR-ZR Ø 0,8	147.020.208	25
23	3,0 m. Liner for wires Ø 0,6/1,0	130.020.302	1	35	Contact Tip M6x30 CU-CR-ZR Ø 1,0	147.020.210	25
23	4,0 m. Liner for wires Ø 0,6/1,0	130.020.402	1	36	Elastic Ring	101.101.102	20
23*	3,0 m. Liner for wires Ø 1,0/1,2	130.050.302	1	37	Gas Diffuser	118.102.117	5

(*) Standard

(*) Standard

DM.3 - DELFOMIG - AIR


AIR COOLED TORCHES



DM.3 DELFOMIG AIR

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating CO²:	340A.
Rating mixed Gas (M21):	220 A.
Duty Cycle:	60%
Wire Size:	Ø 0,8-1,2 mm



COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM3.3	500.080.307	3 m.
DM3.4	500.080.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Std. Øi. 16	179.105.115	5	20	Back cable support	156.101.103	1
2	Tapered Nozzle Øi. 13	179.109.124	5	21	Back cable support screw	181.106.101	20
3	Cylindric Nozzle Øi. 20	179.104.112	5	24	3,0 m. Liner for wires Ø 0,6/1,0	130.020.302	1
5	Contact Tip M8x40 CU Ø 0,8	147.010.108	25	24	4,0 m. Liner for wires Ø 0,6/1,0	130.020.402	1
5*	Contact Tip M8x40 CU Ø 1,0	147.010.110	25	24*	3,0 m. Liner for wires Ø 1,0/1,2	130.050.302	1
5	Contact Tip M8x40 CU Ø 1,2	147.010.112	25	24*	4,0 m. Liner for wires Ø 1,0/1,2	130.050.402	1
5	Contact Tip M8x40 CU-CR-ZR Ø 0,8	147.020.108	25	24	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
5	Contact Tip M8x40 CU-CR-ZR Ø 1,0	147.020.110	25	24	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
5	Contact Tip M8x40 CU-CR-ZR Ø 1,2	147.020.112	25	24	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
6	Gas Diffuser	118.102.119	5	24	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
7	Elastic Ring	101.101.105	20	25	Locking ring	127.102.102	5
8	Torch body with insulator	516.103.006	1	26	Euro Connector	142.105.113	1
9	Wukon insulating tube	140.104.204	1	27	Liner Nut	117.101.101	10
11	Handle "DM" series	537.100.111	1	30	Spring (handle side)	141.106.116	1
12	Handle case screw	181.103.108	20	31	Spring (connector side)	141.106.107	1
13	Complete bladeswitch	146.101.112	5	33	Connector locking ring	127.105.101	1
19	Complete coaxial cable 3m.	508.350.302	1	34	Knuckle joint	156.102.109	1
19	Complete coaxial cable 4m.	508.350.402	1				

(*) Standard

(*) Standard

DM.4 - DELFOMIG - AIR


AIR COOLED TORCHES



DM.4 DELFOMIG AIR

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating CO ₂ :	400A.
Rating mixed Gas (M21):	300 A.
Duty Cycle:	60%
Wire Size:	Ø 0,8-1,6 mm



COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM4.3	500.100.307	3 m.
DM4.4	500.100.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Std. Øi. 17	179.105.113	5	19	Complete coaxial cable 3m.	508.500.302	1
2	Tapered Nozzle Øi. 16	179.109.112	5	19	Complete coaxial cable 4m.	508.500.402	1
3	Cylindric Nozzle Øi. 22	179.104.108	5	20	Back cable support	156.101.103	1
5	Contact Tip M8x40 CU Ø 0,8	147.010.108	25	21	Back cable support screw	181.106.101	20
5	Contact Tip M8x40 CU Ø 1,0	147.010.110	25	24	3,0 m. Liner for wires Ø 1,0/1,2	130.030.302	1
5*	Contact Tip M8x40 CU Ø 1,2	147.010.112	25	24	4,0 m. Liner for wires Ø 1,0/1,2	130.030.402	1
5	Contact Tip M8x40 CU Ø 1,4	147.010.114	25	24*	3,0 m. Liner for wires Ø 1,2/1,6	130.040.302	1
5	Contact Tip M8x40 CU Ø 1,6	147.010.116	25	24*	4,0 m. Liner for wires Ø 1,2/1,6	130.040.402	1
5	Contact Tip M8x40 CU-CR-ZR Ø 0,8	147.020.108	25	24	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
5	Contact Tip M8x40 CU-CR-ZR Ø 1,0	147.020.110	25	24	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
5	Contact Tip M8x40 CU-CR-ZR Ø 1,2	147.020.112	25	24	3,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	134.070.302	1
5	Contact Tip M8x40 CU-CR-ZR Ø 1,4	147.020.114	25	24	4,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	130.070.402	1
5	Contact Tip M8x40 CU-CR-ZR Ø 1,6	147.020.116	25	24	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
6	Gas Diffuser	118.102.122	5	24	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
7	Elastic Ring	101.101.103	20	25	Locking ring	127.102.102	5
8	Torch body with insulator	516.103.007	1	26	Euro Connector	142.105.113	1
9	Wukon insulating tube	140.104.205	1	27	Liner Nut	117.101.101	10
11	Handle "DM" series	537.100.111	1	30	Spring (handle side)	141.106.116	1
12	Handle case screw	181.103.108	20	31	Spring (connector side)	141.106.107	1
13	Complete bladeswitch	146.101.112	5	32	Connector locking ring	156.102.109	1
				33	Knuckle joint	127.105.101	1

(*) Standard

(*) Standard

TW.2 - DELFOMIG - AIR


AIR COOLED TORCHES
WITH TWECO® COMPATIBLE CONSUMABLES



TW.2 DELFOMIG AIR

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating CO²:	290A.
Rating mixed Gas (M21):	250 A.
Duty Cycle:	60%
Wire Size:	Ø 0,8-1,2 mm



COMPLETE TORCH P/N

MOD	P/N	LENGTH
TW2.3	500.551.307	3 m.
TW2.4	500.551.407	4 m.

LISTA RICAMBI

POS.	DESCRIPTION	P/N	BAG.	POS.	DESCRIPTION	P/N	BAG.
1*	Conic nozzle Øi. 16	24CT-62-S	2	16	Euro Connector	142.105.502	1
2	Nozzle insulator	34CT	2	17	4,5 m. Liner for wires Ø 0,8/1,2	42-4045-15	1
3	Contact Tip CU Ø 0,8	14H-35	25	18	Liner Nut	117.101.501	10
3	Contact Tip CU Ø 1,0	14H-40	25	19	Nozzle Stnd. Øi. 15	179.105.114	5
3*	Contact Tip CU Ø 1,2	14H-45	25	19	Tapered Nozzle Øi. 12	179.109.118	5
4	Gas Diffuser	52FN	5	20	Contact Tip M8x40 CU Ø 0,8	147.010.108	25
5	Torch body with insulator	516.103.506	1	20	Contact Tip M8x40 CU Ø 1,0	147.010.110	25
6	Handle "DM" series	537.100.111	1	20	Contact Tip M8x40 CU Ø 1,2	147.010.112	25
7	Complete bladeswitch	146.101.112	5	20	Contact Tip M8x40 CU-CR-ZR Ø 0,8	147.020.108	25
8	Handle case screw	181.103.108	20	20	Contact Tip M8x40 CU-CR-ZR Ø 1,0	147.020.110	25
9	Knuckle joint	156.102.109	1	20	Contact Tip M8x40 CU-CR-ZR Ø 1,2	147.020.112	25
10	Spring (handle side)	141.106.116	1	21	Gas Diffuser	118.102.510	5
11	Complete coaxial cable 3m.	508.350.302	1				
11	Complete coaxial cable 4m.	508.350.402	1				
12	Spring (connector side)	141.106.107	1				
13	Back cable support	156.101.103	1				
14	Back cable support screw	181.106.101	20				
15	Locking ring	127.102.102	5				

(*) Standard

(*) Standard

TW.4 - DELFOMIG - AIR


AIR COOLED TORCHES
WITH TWECO® COMPATIBLE CONSUMABLES



TW.4 DELFOMIG AIR

TECHNICAL DATA

Technical data: (EN60974-7)
Rating CO₂: 400A.
Rating mixed Gas (M21): 340 A.
Duty Cycle: 60%
Wire Size: Ø 1,0-1,6 mm



COMPLETE TORCH P/N

MOD	P/N	LENGTH
TW4.3	500.561.307	3 m.
TW4.4	500.561.407	4 m.

REPLACEMENT PARTS							
POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Conic nozzle Øi. 16	24CT-62-S	2	16	Euro Connector	142.105.502	1
2	Nozzle insulator	34CT	2	17	4,5 m. Liner for wires Ø 0,8/1,2	44-3545-15	1
3	Contact Tip CU Ø 0,8	14H-35	25	17	4,5 m. Liner for wires Ø 1,2/1,6	44-116-15	1
3	Contact Tip CU Ø 1,0	14H-40	25	18	Liner Nut	117.101.501	10
3*	Contact Tip CU Ø 1,2	14H-45	25	19	Nozzle Stnd. Øi. 17	179.105.121	5
3	Contact Tip CU Ø 1,3	14H-52	25	19	Tapered Nozzle Øi. 15	179.109.110	5
3	Contact Tip CU Ø 1,6	14H-116	25	20	Contact Tip M8x40 CU Ø 0,8	147.010.108	25
4	Gas Diffuser	54A	5	20	Contact Tip M8x40 CU Ø 1,0	147.010.110	25
5	Torch body with insulator	516.103.507	1	20	Contact Tip M8x40 CU Ø 1,2	147.010.112	25
6	Handle "DM" series	537.100.111	1	20	Contact Tip M8x40 CU Ø 1,6	147.010.116	25
7	Complete bladeswitch	146.101.112	5	20	Contact Tip M8x40 CU-CR-ZR Ø 0,8	147.020.108	25
8	Handle case screw	181.103.108	20	20	Contact Tip M8x40 CU-CR-ZR Ø 1,0	147.020.110	25
9	Knuckle joint	156.102.109	1	20	Contact Tip M8x40 CU-CR-ZR Ø 1,2	147.020.112	25
10	Spring (handle side)	141.106.116	1	20	Contact Tip M8x40 CU-CR-ZR Ø 1,6	147.020.116	25
11	Complete coaxial cable 3m.	508.500.302	1	21	Gas Diffuser	118.102.511	5
11	Complete coaxial cable 4m.	508.500.402	1				
12	Spring (connector side)	141.106.107	1				
13	Back cable support	156.101.103	1				
14	Back cable support screw	181.106.101	20				
15	Locking ring	127.102.102	5				

(*) Standard


DELFO MIG - LIQUID

LIQUID COOLED TORCHES

BEING DIFFERENT

PREMIUM QUALITY

MADE IN ITALY



New liquid cooling system
increased by 60%

- » New ergonomic handle with "Grip" insert for best accessibility - optimum balance.
- » New nozzle-holder with mettalic protection, for greater durability and heat resistance.
- » New ball joint with optimum movement radius.



DM.27 - DELFOMIG - LIQUID


LIQUID COOLED TORCHES



DM.27 DELFOMIG LIQUID

TECHNICAL DATA

Technical data: (EN60974-7)
Rating CO₂: 300 A.
Rating mixed Gas (M21): 270 A.
Duty Cycle: 100%
Wire Size: Ø 0,8 -1,2 mm
Torch input pressure: Min. 2,5 bar
 (Max. 3,5 bar)
Min. flow rate: 1,3 l/min.



COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM27.3	501.070.307	3 m.
DM27.4	501.070.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Std. Øi. 15	179.105.110	5	21	Cable assembly 4m.	523.002.402	1
2	Tapered Nozzle Øi. 12	179.109.117	5	22	Back cable support	156.101.106	1
3	Cylindric Nozzle Øi. 18	179.104.105	5	23	Back cable support screw	181.103.103	20
4	Contact Tip M8x30 CU Ø 0,8	147.010.308	25	24	Water out hose "black"	166.081.051	1
4	Contact Tip M8x30 CU Ø 1,0	147.010.310	25	26	Euro Connector	142.105.121	1
4	Contact Tip M8x30 CU Ø 1,2	147.010.312	25	28	Locking ring	127.102.102	5
4	Contact Tip M8x30 CU-CR-ZR Ø 0,8	147.020.308	25	29	Liner Nut	117.101.101	10
4	Contact Tip M8x30 CU-CR-ZR Ø 1,0	147.020.310	25	30*	3,0 m. Liner for wires Ø 1,0/1,2	130.050.302	1
4*	Contact Tip M8x30 CU-CR-ZR Ø 1,2	147.020.312	25	30*	4,0 m. Liner for wires Ø 1,0/1,2	130.050.402	1
5	Elastic ring	101.101.104	20	30	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
8	Handle "DM" series	537.100.111	1	30	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
9	Handle case screw	181.103.108	20	30	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
10	Wukon insulating tube	140.104.112	1	30	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
11	Complete bladeswitch	146.101.112	5	31	Quick Connector	150.108.115	10
13	Liner Carrier 3m.	145.050.301	1	32	Gas Diffuser	118.103.105	5
13	Liner Carrier 4m.	145.050.401	1	33	Insulating ring	151.105.107	10
16	Power Cable 3m.	512.100.301	1	34	Nozzle holder	150.112.103	1
16	Power Cable 4m.	512.100.401	1	35	Hose clamp Ø 9,5	101.106.202	10
17	Water in hose "blue"	202.081.051	1	36	Torch body with nozzle holder	516.116.105	1
18	Control cable	143.101.102	1	37	Spring (connector side)	141.106.109	1
20	Protective cover	175.300.280	1	39	Spring (handle side)	141.106.115	1
21	Cable assembly 3m.	523.002.302	1	40	Knuckle joint	156.102.109	1

(*) Standard

DM.30 - DELFOMIG - LIQUID


LIQUID COOLED TORCHES

DM.30 DELFOMIG LIQUID



TECHNICAL DATA

Technical data: (EN60974-7)
Rating CO₂: 330 A.
Rating mixed Gas (M21): 300 A.
Duty Cycle: 100%
Wire Size: Ø 0,8 -1,2 mm
Torch input pressure: Min. 2,5 bar
 (Max. 3,5 bar)
Min. flow rate: 1,3 l/min.



COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM30.3	501.080.307	3 m.
DM30.4	501.080.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Std. Øi. 15	179.105.114	5	21	Cable assembly 4m.	523.001.402	1
2	Tapered Nozzle Øi. 12	179.109.118	5	22	Back cable support	156.101.106	1
3	Cylindric Nozzle Øi. 18	179.104.109	5	23	Back cable support screw	181.103.103	20
4	Contact Tip M8x40 CU ø 0,8	147.010.108	25	24	Water out hose "black"	166.081.051	1
4	Contact Tip M8x40 CU ø 1,0	147.010.110	25	26	Euro Connector	142.105.123	1
4	Contact Tip M8x40 CU ø 1,2	147.010.112	25	28	Locking ring	127.102.102	5
4	Contact Tip M8x40 CU-CR-ZR ø 0,8	147.020.108	25	29	Liner Nut	117.101.101	10
4	Contact Tip M8x40 CU-CR-ZR ø 1,0	147.020.110	25	30*	3,0 m. Liner for wires Ø 1,0/1,2	130.050.302	1
4*	Contact Tip M8x40 CU-CR-ZR ø 1,2	147.020.112	25	30*	4,0 m. Liner for wires Ø 1,0/1,2	130.050.402	1
5	Elastic ring	101.101.104	20	30	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
8	Handle "DM" series	537.100.111	1	30	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
9	Handle case screw	181.103.108	20	30	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
10	Wukon insulating tube	140.104.112	1	30	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
11	Complete bladeswitch	146.101.112	5	31	Quick Connector	150.108.115	10
13	Liner Carrier 3m.	145.050.301	1	32	Gas Diffuser	118.103.105	5
13	Liner Carrier 4m.	145.050.401	1	33	Insulating ring	151.105.107	10
14	Gas hose "black"	166.081.051	1	34	Nozzle holder	150.112.103	1
15	Hose clamp Ø 9,5	101.106.202	10	35	Hose clamp Ø 9,5	101.106.202	10
16	Power Cable 3m.	512.100.301	1	36	Torch body with nozzle holder	516.116.104	1
16	Power Cable 4m.	512.100.401	1	37	Spring (connector side)	141.106.109	1
17	Water in hose "blue"	202.081.051	1	39	Spring (handle side)	141.106.115	1
18	Control cable	143.101.102	1	40	Knuckle joint	156.102.109	1
20	Protective cover	175.300.280	1				
21	Cable assembly 3m.	523.001.302	1				

(*) Standard

DM.50 - DELFOMIG - LIQUID


LIQUID COOLED TORCHES TIP M8X30



DM.50 DELFOMIG LIQUID

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating CO ₂ :	500 A.
Rating mixed Gas (M21):	450 A.
Duty Cycle:	100%
Wire Size:	Ø 0,8 -1,6 mm
Pressione d'esercizio:	Min. 2,5 bar (Max. 3,5 bar)
Min. flow rate:	2,0 l/min.



TIP M8X30

COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM50.3	501.111.307	3 m.
DM50.4	501.111.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Std. Øi. 17	179.105.121	5	21	Cable assembly 4m.	523.001.402	1
2	Tapered Nozzle Øi. 15	179.109.110	5	22	Back cable support	156.101.106	1
3	Cylindric Nozzle Øi. 22	179.104.108	5	23	Back cable support screw	181.103.103	20
4	Contact Tip M8x30 CU ø 0,8	147.010.308	25	24	Water out hose "black"	166.081.051	1
4	Contact Tip M8x30 CU ø 1,0	147.010.310	25	26	Euro Connector	142.105.123	1
4	Contact Tip M8x30 CU ø 1,2	147.010.312	25	28	Locking ring	127.102.102	5
4	Contact Tip M8x30 CU ø 1,6	147.010.316	25	29	Liner Nut	117.101.101	10
4	Contact Tip M8x30 CU-CR-ZR ø 0,8	147.020.308	25	30*	3,0 m. Liner for wires Ø 1,0/1,2	189.060.302	1
4	Contact Tip M8x30 CU-CR-ZR ø 1,0	147.020.310	25	30*	4,0 m. Liner for wires Ø 1,0/1,2	189.060.402	1
4*	Contact Tip M8x30 CU-CR-ZR ø 1,2	147.020.312	25	30	3,0 m. Liner for wires Ø 1,2/1,6	189.070.302	1
4	Contact Tip M8x30 CU-CR-ZR ø 1,6	147.020.316	25	30	4,0 m. Liner for wires Ø 1,2/1,6	189.070.402	1
5	Elastic ring	101.101.103	20	30	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
8	Handle "DM" series	537.100.111	1	30	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
9	Handle case screw	181.103.108	20	30	3,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	134.070.302	1
10	Wukon insulating tube	140.104.115	1	30	4,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	134.070.402	1
11	Complete bladeswitch	146.101.112	5	30	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
13	Liner Carrier 3m.	145.050.301	1	30	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
13	Liner Carrier 4m.	145.050.401	1	31	Quick Connector	150.108.115	10
14	Gas hose "black"	166.081.051	1	32	Gas Diffuser	118.103.106	5
15	Hose clamp Ø 9,5	101.106.202	10	33	Insulating ring	151.105.106	10
16	Power Cable 3m.	512.100.301	1	34	Nozzle holder	150.112.102	1
16	Power Cable 4m.	512.100.401	1	35	Hose clamp Ø 9,5	101.106.202	10
17	Water in hose "blue"	202.081.051	1	36	Torch body with nozzle holder	516.116.103	1
18	Control cable	143.101.102	1	37	Spring (connector side)	141.106.115	1
20	Protective cover	175.300.280	1	38	Spring (handle side)	141.106.109	1
21	Cable assembly 3m.	523.001.302	1	39	Knuckle joint	156.102.109	1


DM.50 - DELFOMIG - LIQUID

LIQUID COOLED TORCHES TIP M8X40

DM.50 DELFOMIG LIQUID

TECHNICAL DATA

Technical data: (EN60974-7)
Rating CO₂: 500 A.
Rating mixed Gas (M21): 450 A.
Duty Cycle: 100%
Wire Size: Ø 0,8 -1,6 mm
Pressione d'esercizio: Min. 2,5 bar
 (Max. 3,5 bar)
Min. flow rate: 2,0 l/min.



TIP M8X40

COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM50.3	501.100.307	3 m.
DM50.4	501.100.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Stnd. Øi. 17	179.105.121	5	21	Cable assembly 4m.	523.001.402	1
2	Tapered Nozzle Øi. 15	179.109.110	5	22	Back cable support	156.101.106	1
3	Cylindric Nozzle Øi. 22	179.104.113	5	23	Back cable support screw	181.103.103	20
4	Contact Tip M8x40 CU Ø 0,8	147.010.108	25	24	Water out hose "black"	166.081.051	1
4	Contact Tip M8x40 CU Ø 1,0	147.010.110	25	26	Euro Connector	142.105.123	1
4	Contact Tip M8x40 CU Ø 1,2	147.010.112	25	28	Locking ring	127.102.102	5
4	Contact Tip M8x40 CU Ø 1,6	147.010.116	25	29	Liner Nut	117.101.101	10
4	Contact Tip M8x40 CU-CR-ZR Ø 0,8	147.020.108	25	30*	3,0 m. Liner for wires Ø 1,0/1,2	189.060.302	1
4	Contact Tip M8x40 CU-CR-ZR Ø 1,0	147.020.110	25	30*	4,0 m. Liner for wires Ø 1,0/1,2	189.060.402	1
4*	Contact Tip M8x40 CU-CR-ZR Ø 1,2	147.020.112	25	30	3,0 m. Liner for wires Ø 1,2/1,6	189.070.302	1
4	Contact Tip M8x40 CU-CR-ZR Ø 1,6	147.020.116	25	30	4,0 m. Liner for wires Ø 1,2/1,6	189.070.402	1
5	Elastic ring	101.101.103	20	30	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
8	Handle "DM" series	537.100.111	1	30	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
9	Handle case screw	181.103.108	20	30	3,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	134.070.302	1
10	Wukon insulating tube	140.104.115	1	30	4,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	134.070.402	1
11	Complete bladeswitch	146.101.112	5	30	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
13	Liner Carrier 3m.	145.050.301	1	30	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
13	Liner Carrier 4m.	145.050.401	1	31	Quick Connector	150.108.115	10
14	Gas hose "black"	166.081.051	1	32	Gas Diffuser	118.103.106	5
15	Hose clamp Ø 9,5	101.106.202	10	33	Insulating ring	151.105.106	10
16	Power Cable 3m.	512.100.301	1	34	Nozzle holder	150.112.102	1
16	Power Cable 4m.	512.100.401	1	35	Hose clamp Ø 9,5	101.106.202	10
17	Water in hose "blue"	202.081.051	1	36	Torch body with nozzle holder	516.116.103	1
18	Control cable	143.101.102	1	37	Spring (connector side)	141.106.115	1
20	Protective cover	175.300.280	1	38	Spring (handle side)	141.106.109	1
21	Cable assembly 3m.	523.001.302	1	39	Knuckle joint	156.102.109	1

(*) Standard

DM.55 - DELFOMIG - LIQUID


LIQUID COOLED TORCHES



DM.55 DELFOMIG LIQUID

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating CO₂:	550 A.
Rating mixed Gas (M21):	500 A.
Duty Cycle:	100%
Wire Size:	Ø 0,8 -1,6 mm
Pressione d'esercizio:	Min. 2,5 bar (Max. 3,5 bar)
Min. flow rate:	1,4 l/min.



COMPLETE TORCH P/N

MOD	P/N	LENGTH
DM55.3	501.150.307	3 m.
DM55.4	501.150.407	4 m.

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1*	Nozzle Stnd. Øi. 17	179.105.109	5	24	Power Cable 3m.	512.100.301	1
2	Back Nozzle	179.108.102	5	24	Power Cable 4m.	512.100.401	1
3	Front Nozzle Øi. 17	179.102.102	5	25	Water in hose "blue"	202.081.051	1
4	Nozzle Insulator	103.102.102	5	26	Control cable	143.101.102	1
5	Contact Tip M8x30 CU Ø 0,8	147.010.308	25	28	Protective cover	175.300.280	1
5	Contact Tip M8x30 CU Ø 1,0	147.010.310	25	29	Cable assembly 3m.	523.001.302	1
5	Contact Tip M8x30 CU Ø 1,2	147.010.312	25	29	Cable assembly 4m.	523.001.402	1
5	Contact Tip M8x30 CU Ø 1,6	147.010.316	25	30	Back cable support	156.101.106	1
5	Contact Tip M8x30 CU-CR-ZR Ø 0,8	147.020.308	25	31	Water out hose "black"	166.081.051	1
5	Contact Tip M8x30 CU-CR-ZR Ø 1,0	147.020.310	25	33	Euro Connector	142.105.123	1
5*	Contact Tip M8x30 CU-CR-ZR Ø 1,2	147.020.312	25	35	Locking ring	127.102.102	5
5	Contact Tip M8x30 CU-CR-ZR Ø 1,6	147.020.316	25	36	Liner Nut	117.101.101	10
6	Gas Diffuser	118.103.103	5	37*	3,0 m. Liner for wires Ø 1,0/1,2	189.060.302	1
7	Support insulating ring	151.104.104	10	37*	4,0 m. Liner for wires Ø 1,0/1,2	189.060.402	1
9	Rubber ring	135.101.103	10	37	3,0 m. Liner for wires Ø 1,2/1,6	189.070.302	1
10	Water distributor	119.101.103	10	37	4,0 m. Liner for wires Ø 1,2/1,6	189.070.402	1
11	Rubber ring	135.101.103	10	37	3,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.302	1
12	Pressure ring	151.103.104	10	37	4,0 m. Liner for Al. wires Ø 1,0/1,2 Teflon	134.060.402	1
13	Torch body locking ring	127.101.103	5	37	3,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	134.070.302	1
14	Torch body	516.101.106	1	37	4,0 m. Liner for Al. wires Ø 1,2/1,6 Teflon	134.070.402	1
16	Handle "DM" series	537.100.111	1	37	3,0 m. Liner for Al. wires Ø 0,8/1,0 Carbo	134.030.402	1
17	Handle case screw	181.103.108	20	37	4,0 m. Liner for Al. wires Ø 1,2/1,6 Carbo	134.090.402	1
19	Wukon insulating tube	140.104.116	1	38	Quick Connector	150.108.115	10
20	Complete bladeswitch	146.101.112	5	39	Back cable support screw	181.103.103	20
21	Liner Carrier 3m.	145.050.301	1	40	Hose clamp Ø 9,5	101.106.202	10
21	Liner Carrier 4m.	145.050.401	1	41	Spring (connector side)	141.106.115	1
22	Gas hose "black"	166.081.051	1	42	Spring (handle side)	141.106.109	1
23	Hose clamp Ø 9,5	101.106.202	10	43	Knuckle joint	156.102.109	1

(*) Standard

(*) Standard

DELFO SPECIAL PRODUCT

SERVICE & QUALITY

PREMIUM QUALITY
MADE IN ITALY

SPECIALS

- » Realization of special torches with geometry on request, for welding with limited accessibility.



DELFOTIG

BEING DIFFERENT


PREMIUM QUALITY

MADE IN ITALY

- » New ergonomic handle with "Grip" insert for best accessibility - optimum balance.
- » New series of modular switching and control functions integrated into the handle - Easy application.
- » New ball joint with optimum movement radius.
- » New design of the back box cable support, machine side.

DT.9 / 9V - DELFOTIG - AIR


AIR COOLED TORCHES



DT.9 / 9V DELFOTIG AIR

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating:	110 A. DC
	80 A. AC
Duty Cycle:	35%
Tungsten Electrodes:	0,5-1,6 mm



COMPLETE TORCH P/N

MOD.	EU	DINSE 50MMQ	MEKAFIN
DT.9.4	401.011.040	401.011.041	401.011.043
DT.9.8	401.011.080	401.011.081	401.011.083
DT.9F.4 (Flex)	401.111.040	401.111.041	401.111.043
DT.9F.8 (Flex)	401.111.080	401.111.081	401.111.083
DT.9A.4 (DIRITTA)	401.400.040	401.400.041	-
DT.9A.8 (DIRITTA)	401.400.080	401.400.081	-
DT.9V.4	401.200.040	401.200.041	-
DT.9V.8	401.200.080	401.200.081	-
DT.9VF.4	401.300.040	401.300.041	-
DT.9VF.8	401.300.080	401.300.081	-

REPLACEMENT PARTS							
POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIZIONE	P/N	BAG
1	Long Back cap TIG 9-20	321.102.102	10	11	Valve with "O" ring	330.101.101	1
2	"O" Ring	101.102.112	10	12	"O" ring	101.102.112	10
3	Std. Torch Body	416.103.009	1	13	Flex torch body with Valve	416.108.109	1
4	Flex Torch Body	416.107.009	1	15	Round handle	437.102.101	1
5	Handle with screw	437.101.101	1	16	Knuckle joint	456.102.101	1
6	Single button switch	439.000.101	1	17	Control cable with connector 4m.	443.001.401	1
7	Two buttons switch	439.000.102	1	17	Control cable with connector 8m.	443.001.801	1
8	Four buttons switch	439.000.103	1	18	Power Cable 4m.	324.010.404	1
9	Switch with potentiometer 4,7 Kohm	439.001.004	1	18	Power Cable 8m.	324.010.804	1
9	Switch with potentiometer 10 Kohm	439.001.010	1	19	Protective Cover "Tubix"	175.002.220	1
10	Torch body with Valve	416.105.009	1	20	Power Cable for Valve 4m.	324.020.404	1
				20	Power Cable for Valve 8m.	324.020.804	1
				21	Handle screw	181.104.103	20

DT.17/ 17V - DELFOTIG - AIR


AIR COOLED TORCHES



DT.17 / 17V DELFOTIG AIR

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating:	140A. DC
	100 A. AC
Duty Cycle:	35%
Tungsten Electrodes:	0,5-2,4 mm



COMPLETE TORCH P/N



MOD.	EU	DINSE 50MMQ	MEKAFIN
DT.17.4	410.011.040	410.011.041	410.011.043
DT.17.8	410.011.080	410.011.081	410.011.083
DT.17F.4 (Flex)	410.111.040	410.111.041	410.111.043
DT.17F.8 (Flex)	410.111.080	410.111.081	410.111.083
DT.17V.4	410.200.040	410.200.041	-
DT.17V.8	410.200.080	410.200.081	-
DT.17VF.4	410.300.040	410.300.041	-
DT.17VF.8	410.300.080	410.300.081	-

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1	Long Back cap TIG 17-26-18	321.102.101	10	12	"O" ring	101.102.112	10
2	"O" Ring	101.102.111	10	13	Flex torch body with Valve	416.108.017	1
3	Std. Torch Body	416.103.017	1	14	Round handle	437.102.101	1
4	Flex Torch Body	416.107.017	1	15	Knuckle joint	456.102.101	1
5	Handle with screw	437.101.101	1	16	Control cable with connector 4m.	443.001.401	1
6	Single button switch	439.000.101	1	16	Control cable with connector 8m.	443.001.801	1
7	Two buttons switch	439.000.102	1	17	Power Cable 4m.	324.010.404	1
8	Four buttons switch	439.000.103	1	17	Power Cable 8m.	324.010.804	1
9	Switch with potentiometer 4,7 Kohm	439.001.004	1	18	Protective Cover "Tubix"	175.002.220	1
9	Switch with potentiometer 10 Kohm	439.001.010	1	19	Power Cable for Valve 4m.	324.020.404	1
10	Torch body with Valve	416.105.017	1	19	Power Cable for Valve 8m.	324.020.804	1
11	Valve with "O" ring	330.101.101	1	20	Handle screw	181.104.103	20

DT.26 / 26V - DELFOTIG - AIR

AIR COOLED TORCHES



DT.26 / 26V DELFOTIG AIR

TECHNICAL DATA DT. 26

Technical data:	(EN60974-7)
Rating:	250A. DC 200 A AC
Duty Cycle:	60%
Tungsten Electrodes:	0,5-4,0 mm

TECHNICAL DATA DT.26V

Technical data:	(EN60974-7)
Rating:	180 A. DC 150 A. AC
Duty Cycle:	35%
Tungsten Electrodes:	0,5-4,0 mm

COMPLETE TORCH P/N

MOD.	EU	DINSE 50MMQ	MEKAFIN
DT.26.4	420.011.040	420.011.041	420.011.043
DT.26.8	420.011.080	420.011.081	420.011.083
DT.26F.4 (Flex)	420.111.040	420.111.041	420.111.043
DT.26F.8 (Flex)	420.111.080	420.111.081	420.111.083
DT.26A.4 (Diritta)	420.401.040	420.401.041	
DT.26A.8 (Diritta)	420.401.080	420.401.081	
DT.26V.4 (Valvola)	420.200.040	420.200.041	
DT.26V.8 (Valvola)	420.200.080	420.200.081	
DT.26VF.4 (Valv.Flex)	420.300.040	420.300.041	
DT.26VF.8 (Valv.Flex)	420.300.080	420.300.081	

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIZIONE	P/N	BAG
1	Long Back cap TIG 17-26-18	321.102.101	10	13	Flex torch body with Valve	316.108.502	1
2	"O" Ring	101.102.111	10	14	Round handle	337.102.102	1
3	Std. Torch Body	316.103.502	1	15	Straight torch body	416.106.102	1
4	Flex Torch Body	316.107.502	1	16	Knuckle joint	456.102.102	1
5	Handle with screw	437.101.102	1	17	Power Cable 4m.	325.010.403	1
6	Single button switch	439.000.101	1	17	Power Cable 8m.	325.010.803	1
7	Two buttons switch	439.000.102	1	18	Hose clamp Ø 9,5	101.106.202	20
8	Four buttons switch	439.000.103	1	19	Gas hose "black"	166.081.051	1
9	Switch with potentiometer 4,7 Kohm	439.001.004	1	20	Control cable with connector 4m.	443.001.401	1
9	Switch with potentiometer 10 Kohm	439.001.010	1	20	Control cable with connector 8m.	443.001.801	1
10	Torch body with Valve	316.105.102	1	21	Protective Cover "Tubix"	175.002.285	1
11	Valve with "O" ring	330.101.102	1	22	Power Cable for Valve 4m.	324.030.401	1
12	"O" ring	101.102.112	1	22	Power Cable for Valve 8m.	324.030.801	1
				23	Handle screw	181.104.103	10

DELFO TIG - DETAIL

REMOTE CONTROLS & CONNECTOR

MODULAR SWITCHING AND REMOTE CONTROL




CONNECTOR

- » New design of the back box cable support, machine side.

DT.18 - DELFOTIG - LIQUID


LIQUID COOLED TORCHES



DT.18 DELFOTIG LIQUID

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating:	320A. DC
	230 A. AC
Duty Cycle:	100%
Tungsten Electrodes:	0,5-4,0 mm



COMPLETE TORCH P/N


MOD.	EU	DINSE 50MMQ	MEKAFIN
DT.18.4	430.011.040	430.011.041	430.011.043
DT.18.8	430.011.080	430.011.081	430.011.083
DT.18F.4 (Flex)	430.111.040	430.111.041	430.111.043
DT.18F.8 (Flex)	430.111.080	430.111.081	430.111.083

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1	Long Back cap TIG 17-26-18	321.102.101	10	12	Knuckle joint	456.102.102	1
2	"O" Ring	101.102.111	10	13	Control cable with connector 4m.	443.001.401	1
3	Std. Torch Body	316.102.501	1	13	Control cable with connector 8m.	443.001.801	1
4	Handle with screw	437.101.102	1	14	Gas hose "black"	166.081.051	1
5	Single button switch	439.000.101	1	15	Water hose "black"	202.070.040	1
6	Two buttons switch	439.000.102	1	16	Hose clamp Ø 9,5	101.106.202	10
7	Four buttons switch	439.000.103	1	18	Power Cable 4m.	312.010.403	1
8	Switch with potentiometer 4,7 Kohm	439.001.004	1	18	Power Cable 8m.	312.010.803	1
8	Switch with potentiometer 10 Kohm	439.001.010	1	20	Protective Cover "Tubix"	175.002.285	1
9	Flex torch body	316.107.504	1	23	Handle screw	181.104.103	20
10	Round handle	337.102.102	1				

DT.20 - DELFOTIG - LIQUID

LIQUID COOLED TORCHES



DT.20 DELFOTIG LIQUID

TECHNICAL DATA

Technical data:	(EN60974-7)
Rating:	250A. DC
	180 A. AC
Duty Cycle:	100%
Tungsten Electrodes:	0,5-3,2 mm

COMPLETE TORCH P/N

MOD.	EU	DINSE 50MMQ	MEKAFIN
DT.20.4	440.011.040	440.011.041	440.011.043
DT.20.8	440.011.080	440.011.081	440.011.083
DT.20F.4 (Flex)	440.111.040	440.111.041	440.111.043
DT.20F.8 (Flex)	440.111.080	440.111.081	440.111.083

REPLACEMENT PARTS

POS.	DESCRIPTION	P/N	BAG	POS.	DESCRIPTION	P/N	BAG
1	Long Back cap TIG 9-20	321.102.102	10	13	Control cable with connector 4m.	443.001.401	1
2	"O" Ring	101.102.112	10	13	Control cable with connector 8m.	443.001.801	1
3	Std. Torch Body	416.102.102	1	14	Gas hose "black"	166.060.040	1
4	Handle with screw	437.101.101	1	15	Water hose "black"	202.070.040	1
5	Single button switch	439.000.101	1	16	Hose clamp Ø 9,5	101.106.202	10
6	Two buttons switch	439.000.102	1	18	Power Cable 4m.	312.020.401	1
7	Four buttons switch	439.000.103	1	18	Power Cable 8m.	312.020.801	1
8	Switch with potentiometer 4,7 Kohm	439.001.004	1	20	Protective Cover "Tubix"	175.002.220	1
8	Switch with potentiometer 10 Kohm	439.001.010	1	23	Handle screw	181.104.103	20
9	Flex torch body	416.107.505	1				
12	Knuckle joint	456.102.101	1				



SERVICE & QUALITY

PREMIUM QUALITY


MADE IN ITALY

REPLACEMENT & ACCESSORIES

REPLACEMENT & ACCESSORIES MIG - MAG

Conduit Liners

DESCRIPTION	COLOR	Ø I.D./O.D.	P/N	COIL.
Covered Liner	blue	1,5/4,0	155.024.015	53 m.
Covered Liner	yellow	20/4,8	155.024.820	53 m.
Covered Liner	red	2,0/4,0	155.024.020	53 m.
Covered Liner	white	2,4/4,8	155.024.824	53 m.
Uncovered Liner	-	2,0/4,8	155.014.820	53 m.
Uncovered Liner	-	2,4/4,8	155.014.824	53 m.



Cables, Hoses & Cover for MIG-MAG Torches

DESCRIPTION	COLOR	Ø I.D./O.D.	P/N	COIL.
Control Wire	black / brown	-	143.101.102	200 m.
Water in hose	blue	5,0/8,0	201.081.051	300 m.
Water/Gas Hose	black	5,0/8,0	166.081.051	300 m.
Water in hose	blue	3,5/8,0	202.080.040	100 m.
Water out hose	red	3,5/8,0	168.080.040	100 m.
Water/Gas hose	black	3,5/8,0	166.080.050	100 m.
Protective cover	black	28/31	175.300.280	20 m.


Other Accessories

DESCRIZIONE	CODICE	BAG
Male spring pin for Air Euro connector	183.102.100	10
Male spring pin for Water Euro connector	183.102.103	10
Female plug for Euro connector	183.103.301	10
Male cylindrical lead	124.102.104	10
Female cylindrical lead	124.101.104	10
Trigger lead	124.103.101	10
Gas plug for Euro connector	150.110.101	10
"O" ring for Euro Gas plug	101.102.110	10

REPLACEMENT & ACCESSORIES TIG




WEAR PARTS DELFO TIG 9-20




POS.	DESCRIPTION	P / N	BAG
1	Long Back cap 41V24	321.102.102	10
2	Medium Back cap 41V35	321.102.104	10
3	Short Back cap 41V33	321.101.102	10
4	"o" ring OR 2018	101.102.112	10
5	Collet Ø 1,0 13N21	313.102.010	10
5	Collet Ø 1,6 13N22	313.102.016	10
5	Collet Ø 2,0	313.102.020	10
5	Collet Ø 2,4 13N23	313.102.204	10
5	Collet Ø 3,2 13N24	313.102.032	10
6	Teflon gasket 598882	335.101.102	10
7	Collet Body Ø 1,0 13N26	314.103.010	10
7	Collet Body Ø 1,6 13N27	314.103.016	10
7	Collet Body Ø 2,0	314.103.020	10
7	Collet Body Ø 2,4 13N28	314.103.024	10
7	Collet Body Ø 3,2 13N29	314.103.032	10
8	Alumina Cup Gr.4 13N08	379.102.104	10
9	Alumina Cup Gr.5 13N09	379.102.105	10
10	Alumina Cup Gr.6 13N10	379.102.106	10
11	Alumina Cup Gr.7 13N11	379.102.107	10
12	Alumina Cup Gr.8 13N12	379.102.108	10
13	Alumina Cup Gr.10 13N13	379.102.110	10
14	Alumina Cup Gr.4L 796F71	379.102.204	10
15	Alumina Cup Gr.5L 796F72	379.102.205	10
16	Alumina Cup Gr.6L 796F73	379.102.206	10
17	Alumina Cup Gr.4 XL 796F75	379.102.304	10
18	Alumina Cup Gr.5 XL 796F76	379.102.305	10
19	Alumina Cup Gr.6 XL 796F77	379.102.306	10
20	Collet Body Gas Lens Ø 1,0 45V42	314.104.010	10
20	Collet Body Gas Lens Ø 1,6 45V43	314.104.016	10
20	Collet Body Gas Lens Ø 2,4 45V44	314.104.024	10
20	Collet Body Gas Lens Ø 3,2 45V45	314.104.032	10
21	Alumina Cup Gr.4 53N58 Gas Lens	379.104.104	10
22	Alumina Cup Gr.5 53N59 Gas Lens	379.104.105	10
23	Alumina Cup Gr.6 53N60 Gas Lens	379.104.106	10
24	Alumina Cup Gr.7 53N61 Gas Lens	379.104.107	10

REPLACEMENT & ACCESSORIES TIG



WEAR PARTS DELFOTIG 17-18-26



POS.	DESCRIPTION	P / N	BAG
1	Long Back cap 57Y02	321.102.101	10
2	Medium Back cap 57Y03	321.102.103	10
3	Short Back cap 57Y04	321.101.101	10
4	"o" ring OR 2037	101.102.111	10
5	Teflon gasket	335.103.101	10
6	Collet Ø 1,0 10N22	313.101.010	10
6	Collet Ø 1,6 10N23	313.101.016	10
6	Collet Ø 2,0	313.101.020	10
6	Collet Ø 2,4 10N24	313.101.024	10
6	Collet Ø 3,2 10N25	313.101.032	10
6	Collet Ø 4,0 54N20	313.101.040	10
7	Teflon gasket 18CG	335.101.101	10
8	Collet Body Ø 1,0 10N30	314.101.010	10
8	Collet Body Ø 1,6 10N31	314.101.016	10
8	Collet Body Ø 2,0	314.101.020	10
8	Collet Body Ø 2,4 10N32	314.101.024	10
8	Collet Body Ø 3,2 10N28	314.101.032	10
8	Collet Body Ø 4,0 406488	314.101.040	10
9	Alumina Cup Gr.4 10N50	379.101.104	10
10	Alumina Cup Gr.5 10N49	379.101.105	10
11	Alumina Cup Gr.6 10N48	379.101.106	10
12	Alumina Cup Gr.7 10N47	379.101.107	10
13	Alumina Cup Gr.8 10N46	379.101.108	10
14	Alumina Cup Gr.10 10N45	379.101.110	10
15	Alumina Cup Gr.12 10N44	379.101.112	10
16	Alumina Cup Gr.5L 10N49L	379.101.205	10
17	Alumina Cup Gr.6L 10N48L	379.101.206	10
18	Alumina Cup Gr.7L 10N47L	379.101.207	10
19	Teflon gasket	335.102.101	10
20	Collet Body Gas Lens Ø 1,0 45V24	314.102.010	10
20	Collet Body Gas Lens Ø 1,6 45V25	314.102.016	10
20	Collet Body Gas Lens Ø 2,4 45V26	314.102.024	10
20	Collet Body Gas Lens Ø 3,2 45V27	314.102.032	10
20	Collet Body Gas Lens Ø 4,0 45V28	314.102.040	10
21	Alumina Cup Gr.4 54N18 Gas Lens	379.103.104	10
22	Alumina Cup Gr.5 54N17 Gas Lens	379.103.105	10
23	Alumina Cup Gr.6 54N16 Gas Lens	379.103.106	10
24	Alumina Cup Gr.7 54N15 Gas Lens	379.103.107	10
25	Alumina Cup Gr.8 54N14 Gas Lens	379.103.108	10
26	Alumina Cup Gr.12 54N19 Gas Lens	379.103.112	10
27	Alumina Cup Gr.5 L 54N17L Gas Lens	379.103.205	10
28	Alumina Cup Gr.6 L 54N16L Gas Lens	379.103.206	10
29	Alumina Cup Gr.7 L 54N15L Gas Lens	379.103.207	10

REPLACEMENT & ACCESSORIES TIG



Cables, Hoses & Cover for Tig Torches

DESCRIPTION	COLOR	Ø I.D/O.D.	P / N	COIL / BAG
Control Wire	black / brown	-	143.101.102	200 m.
Gas Hose TIG 20	black	4,0/6,0	166.060.040	250 m.
Gas Hose TIG 26-18	black	5,0/8,0	166.081.051	300 m.
Water Hose	black	4,0/7,0	202.070.040	100 m.
Protective Cover "Tubix" 9-17-20	-	-	175.002.220	81 m.
Protective Cover "Tubix" 18-26	-	-	175.002.285	81 m.
Rubber Protective Cover 9-17-20	-	-	173.230.210	
Rubber Protective Cover 18-26	-	-	173.280.260	
Leather Protective Cover 9-17-20	black	-	464.019.021	0,8 m.
Leather Protective Cover 18-26	black	-	464.019.026	0,8 m.
Knuckle joint for leather cover 9-17-20	-	-	456.103.101	1
Knuckle joint for leather cover 18-26	-	-	456.103.102	1

Tig torch connectors

TIG CONNECTOR	TORCH MODEL	P / N	BAG
	DT.9-17	442.100.104	1
	SA.9-9V		
	SA.17-17V		
	SA.26V		
	DT.26	442.100.105	1
	SA.26		
	DT.20 - SA.20	442.100.110	1
	DT.18 - SA.18	442.100.111	
	DT.9-17	342.105.107	1
	SA.9-17		
	DT.26	342.105.109	1
	SA.26		
	DT.18-20	342.105.108	1
	SA.18-20		

REPLACEMENT & ACCESSORIES

TUNGSTEN ELECTRODES

ELECTRODES DIFFERENCES

PURE TUNGSTEN WP

WP pure tungsten electrodes (minimum tungsten content is 99.5%, with no other impurities) were the first to be used in TIG welding. The pure tungsten electrode is the best choice for AC welding, even if they can be used in DC. It keeps the surface of the base material particularly clean, has a good conductivity and by heating it tends to assume a regular circular shape, a characteristic that does not make continuous sharpening necessary during use. The welding arc is stable even with very low current, so that aluminum, magnesium and other metals can be welded even with currents below 5 amperes.

CERIATED TUNGSTEN WC20

Ceriated tungsten electrode contains 1.8%-2.2% ceria, electron work is 2.4eV. This electrode plays a good performance on starting arc and stabilizing arc with low current. Therefore, ceriated tungsten electrode are commonly using in pipeline, stainless steel and small precision parts welding. And it's the first choice when the condition is in the low and direct current or the diameter demands below 2.0mm. The mobility of cerium oxide is quite high, so, ceriated tungsten is not suitable for the application in the high current. If it's used in the high current, the oxide may accelerate to the high hot area, which is the top of the tungsten electrode, and the uniformity of oxide may suffer damage, the benefit brought by cerium oxide will disappear.

TUNGSTEN WL 10 LANTHANATED 1%

TUNGSTEN WL 15 LANTHANATED 1,5%

TUNGSTEN WL 20 LANTHANATED 2%

Lanthanated tungsten electrodes contains 0,8 -2,2% lanthanum, the electron work function is 2,8 eV 3,0 eV. Electrodes very easy to start, with very good stability at low current, it is mainly used in DC, with good performance well in AC welding. Lanthanum, with good creep resistance, strong ductility, lower stirring rate, keeps the tip temperature of electrodes lower, which helps to prevent grain from becoming larger, and the service life of electrode can be increased substantially. The lifetime of lanthanated tungsten electrodes is longer than thoriated tungsten. It is particularly good at preventing thermal shock. Also in the short cycle welding when you ignite repeatedly, it can be welded very well and prevent pollution. When welding pipeline, welders are satisfied with this lanthanated tungsten electrodes, because the downtime will be reduce.

TUNGSTEN WS2 RARE HEARTH

TUNGSTEN WS3 RARE HEARTH

Tungsten Electrodes with rare earth (mixed oxides). In comparison to thoriated electrodes this electrode is less harmful to the environment and not radioactive. The electrodes offer excellent ignition characteristics and consistent welding properties. They are universal and suitable for all applications in the whole range of DC and AC welding, for non-alloyed and high-alloyed steel, aluminum, titanium, nickel, copper and magnesium alloys. With their great ignition property, they are suitable for automated welding. Due to the low electrode temperature, they offer an increased current carrying capacity and long service life than thoriated electrodes.

THE ADVANTAGES AT A GLANCE:

- » The welder is no longer exposed to radiation.
- » Reduced environment impact. Remaining pieces and grinding dust are no longer treated as hazardous.
- » No special safeguards required for storage and transport.
- » Electrode tip remains "cooler" than thoriated types
- » Superior repeatable ignition
- » Increased arc stability
- » Reduced burn off
- » Higher current carrying capacity
- » Lower degradation to the electrode tip
- » Increased application flexibility



ELECTRODE LENGHT 175 MM Ø	PURE TUNGSTEN WP	TUNGSTEN CERIATED WC20 2%	TUNGSTEN WL 10 LANTHANATED 1%	TUNGSTEN WL 15 LANTHANATED 1,5%	TUNGSTEN WL 20 LANTHANATED 2%	TUNGSTENO WS2 RARE HEARTH	TUNGSTENO WS3 RARE HEARTH
1,0	300.017.510	300.217.510	300.317.510	300.417.510	300.517.510	300.617.510	300.717.510
1,6	300.017.516	300.217.516	300.317.516	300.417.516	300.517.516	300.617.516	300.717.516
2,4	300.017.524	300.217.524	300.317.524	300.417.524	300.517.524	300.617.524	300.717.524
3,2	300.017.532	300.217.532	300.317.532	300.417.532	300.517.532	300.617.532	300.717.532
4,0	300.017.540	300.217.540	300.317.540	300.417.540	300.517.540	300.617.540	300.717.540

NOTE



DELFO S.r.l.

Via Benaco, 1/3 - 20098
San Giuliano Milanese - Milano - Italy
Tel.: +39 02 87205264

e-mail: info@delfoweld.com
www.delfoweld.com